

# anish granulation lines



Model	AGL-lab	AGL-Pilot	AGL-150	AGL-300	AGL-400	AGL-600	AGL-800	AGL-1000	AGL-1200	AGL-1500	AGL-2000	AGL-2500
Capacity* (Kg)	300 gm to 5 Kg	2.5 to 50 kg	30 to 60 Kg	60 to 120 Kg	75 to 150 kg	120 to 250 Kg	150 to 300 kg	200 to 400 kg	250 to 500 kg	300 to 600 kg	400 to 800 kg	500 to 1000 kg

\*Bulk density = 0.5

## AVAILABLE OPTIONS

### Convertible Combo Fluid Bed Processor:

- Drying
- Top Spray
- Bottom Spray
- Tangential Spray



### Sifting & Milling:

- Vibratory Sifter
- Rotary Turbo Sifter
- Wet & Dry Combo Mill
- Inline Underdriven Comill
- Multi-mill
- Delumping Station

### Product Charging & Discharging:

- IPC Bin & Solution Tank Lifter
- Tipper for Fluid Bed Bowl Unloading
- Multipurpose Column
- Vacuum Transfer System

### Blending:

- Conta-pillar Blender
- Octagonal Blender
- V Blender
- Double Cone Blender

# anish granulation lines



**anish standard granulation line**

Stand-alone installation | High yield and less product loss due to closed transfer by dust-free charging and discharging



**anish lab equipment**

Compact design | Flexible batch size by using exchange bowls | Advanced control system



**anish smart granulation line**

4X productivity compared to Standard Granulation Line  
Through-the-wall installation

2 BAR 12 BAR

FDA  
21CFR PART11  
Compliant

**GAMP 5**  
Category 4 Compliant

CE  
Compliant

UL  
Compliant

Ex  
ATEX