



Ideal for drying of fine particles

Equipment intended to be used for:

- · Drying of Granules
- Drying of API


Salient Features:

- 2 Bar/12 Bar pressure shock resistant construction
- · Auto Bag shaking with telescopic cylinder.
- · Safety interlocks for operational ease.
- · Consistent batch results
- Reproducibility with same parameters for every batch
- Inlet & product bed temperature control ± 2°C



- CFM Control: ± 50-70
- SCADA with 21 CFR part-11 compliance
- Customized BMR/ print parameter format as per requirement
- Desired LOD can be achieved with the help of utilities
- Suitable for aqueous & solvent base formulations
- · SHE policies compliant
- FLP/Atexproof Instrumentation & compliance available





Models:

	R&D Model			Pilot Model			Commercial Model		
	AFBD- 5	AFBD- 25	AFBD- 50	AFBD- 125	AFBD- 250	AFBD- 500	AFBD- 800	AFBD- 1300	AFBD- 1500
Product container volume (in litre)	5	25	50	125	250	500	800	1300	1500

All models are available in 2 bar as well as 12 bar pressure shock resistant construction.

Additional desired features:

- BBD /SFM Sensor will be provided with adjustable sensitivity.
- Conidure sieve can be implemented as per requirement.
- Antistatic accessories can be implemented as per requirement.
- Product container with Discharge mechanism
- Latest version of PLC Configuration to achieve precise parameter controls



anish pharma equip pvt. ltd.

Works: G-68, MIDC Ambad, Nasik, Maharashtra, India 422010 Tel.: +91 253 2381831/2380337

Tel.: +91 253 2381831/2380337 Fax: +91 253 2380903 Office: B-613, Lodha Supremus Tower II, Wagle Estate, Thane (W), Maharashtra, India 400604 T.: +91 22 49765310/311

E: marketing@anishpharma.com | M:+91 8380033063 / +91 8380033064 W: www.anishpharma.com